


Metro Industries, Inc. Standard Rubber Washers for Standard Screw Size										<u>Material:</u>		<u>Neoprene</u>			
OD	ID	Thickness	Screw Siz	StyleCode	Qty	Price/PC	Qty	Price/PC	Qty	Price/PC	Qty	Price/PC	Qty	Price/PC	
0.375	0.125	0.063	No. 6	A60BK-0375-0125-0063	500	\$0.220	1,000	\$0.115	2,500	\$0.078	5,000	\$0.044	25,000	\$0.035	
0.406	0.156	0.063	No. 8	A60BK-0406-0156-0063	500	\$0.220	1,000	\$0.118	2,500	\$0.081	5,000	\$0.046	25,000	\$0.037	
0.421	0.171	0.063	No. 10	A60BK-0421-0171-0063	500	\$0.220	1,000	\$0.118	2,500	\$0.081	5,000	\$0.046	25,000	\$0.037	
0.547	0.171	0.094	No. 10	A60BK-0547-0171-0094	500	\$0.220	1,000	\$0.123	2,500	\$0.083	5,000	\$0.048	25,000	\$0.039	
0.562	0.191	0.094	No. 12	A60BK-0567-0191-0094	500	\$0.220	1,000	\$0.125	2,500	\$0.085	5,000	\$0.050	25,000	\$0.041	
0.609	0.234	0.094	1/4"	A60BK-0609-0234-0094	500	\$0.220	1,000	\$0.125	2,500	\$0.085	5,000	\$0.050	25,000	\$0.041	
0.668	0.291	0.094	5/16"	A60BK-0671-0291-0094	500	\$0.220	1,000	\$0.128	2,500	\$0.088	5,000	\$0.050	25,000	\$0.041	
0.734	0.359	0.094	3/8"	A60BK-0734-0359-0094	500	\$0.220	1,000	\$0.128	2,500	\$0.088	5,000	\$0.052	25,000	\$0.043	
0.859	0.491	0.094	1/2"	A60BK-0859-0491-0094	500	\$0.220	1,000	\$0.132	2,500	\$0.088	5,000	\$0.052	25,000	\$0.043	
0.983	0.609	0.094	5/8"	A60BK-0981-0609-0094	500	\$0.220	1,000	\$0.132	2,500	\$0.095	5,000	\$0.052	25,000	\$0.043	
1.125	0.75	0.094	3/4"	A60BK-1125-0750-0094	500	\$0.220	1,000	\$0.132	2,500	\$0.095	5,000	\$0.052	25,000	\$0.043	
1.375	1	0.094	1"	A60BK-1375-1000-0094	500	\$0.220	1,000	\$0.132	2,500	\$0.095	5,000	\$0.052	25,000	\$0.043	
0.859	0.359	0.125	3/8"	A60BK-0859-0359-0125	500	\$0.220	1,000	\$0.158	2,500	\$0.125	5,000	\$0.095	25,000	\$0.045	
1	0.491	0.125	1/2"	A60BK-1000-0491-0125	500	\$0.220	1,000	\$0.158	2,500	\$0.125	5,000	\$0.095	25,000	\$0.045	
1.109	0.609	0.125	5/8"	A60BK-1109-0609-0125	500	\$0.220	1,000	\$0.158	2,500	\$0.125	5,000	\$0.095	25,000	\$0.045	
1.25	0.75	0.125	3/4"	A60BK-1250-0750-0125	500	\$0.220	1,000	\$0.158	2,500	\$0.125	5,000	\$0.095	25,000	\$0.045	
1.5	1	0.125	1"	A60BK-1500-1000-0125	500	\$0.220	1,000	\$0.158	2,500	\$0.125	5,000	\$0.095	25,000	\$0.045	



Tolerances	
Thickness	OD & ID
.031" <= +/- .010"	.000" - .499" = +/- .015"
.032" - .061" = +/- .012"	.500" - .999" = +/- .020"
.062" - .124" = +/- .016"	1.000" - 1.499" = +/- .025"
.125" - .187" = +/- .020"	1.500" - 1.999" = +/- .030"
.187" - .374" = +/- .031"	2.000" - 2.499" = +/- .035"
.375" - .500" = +/- .047"	2.500" - 2.999" = +/- .035"

Material Specifications	
Neoprene	
Durometer	60 +/-5
Tensile	500 PSI
Elongation	250%
Low Temp	-25 F
High Temp	-225 F
EPDM	
Durometer	60 +/-5
Tensile	500 PSI
Elongation	250%
Low Temp	-25 F
High Temp	225 F
Buna-N	
Durometer	60 +/-5
Tensile	500 PSI
Elongation	250%
Low Temp	-25 F
High Temp	+225 F

Material Specifications	
Silicone	
Durometer	60 +/-5
Tensile	700 PSI
Elongation	300%
Low Temp	-40 F
High Temp	+400 F
FKM (Viton™)	
Durometer	75 +/-5
Tensile	800 PSI
Elongation	250%
Low Temp	-25 F
High Temp	+500 F
FDA White Nitrile	
Durometer	55 +/-10
Tensile	700 PSI
Elongation	300%
Low Temp	-25 F
High Temp	+225 F

\*Properties Listed are Typical Values and do not imply a warranty  
 \*\*Pricing Subject to Change without Notice  
 \*\*\*Customer is responsible for testing to ensure fit, form and function.